

ALL ALUMINIUM SEMI-SEALED ROOFING AND CLADDING RIVETS

AT LAST! A FOOL-PROOF, EASY TO USE, ALL ALUMINIUM 4mm SEMI-SEALED, MULTI GRIP RIVET FOR FIXING FLASHINGS AND 100 OTHER USES IN THE ROOFING INDUSTRY!

FEATURES	BENEFITS
4mm body	Same sized body as before
Pre-drill 4.1mm pilot hole	Ability to use the same drill bits
Aluminium mandrel	No rusting if dropped or left on a roof or in a gutter
Stem locking system	Eliminates the risk of mandrel head vibrating loose, while providing increased strength and a weather resistant joint
Grip range 1.2mm – 4.8mm	Works well with multiple material thicknesses Reduces inventories and eliminates operator error
Shear strength = 845N	Same strength as old system
Tensile strength = 1025N	Same strength as old system
Soft set system	Easy to pull up and set correctly
No touch up paint needed!	27 Common colours available ex-stock
Bulbing formation	Will fit oversize or irregular holes, providing extra strength and vibration resistance
Semi sealed body	No need to place silicone on rivet head once set

SPECIFICATIONS

GRIP RANGE (L)	HEAD DIAMETER (H)	HEAD THICKNESS (T)	STANDARD STRENGTH N (NOM.)	
			SHEAR	TENSILE
1.2 – 4.8mm	7.9mm	1.27mm	1000	1600

AVAILABLE COLOURS

Matched to



COLORSTEEL®

